

| Folder  | Comments  | Non-inherited Permissions  |
|---|---|--|
| <b>ConfigMgr</b>  |   | Share: <ul style="list-style-type: none"> <li>• Everyone, Full</li> </ul> NTFS: <ul style="list-style-type: none"> <li>• Local Admins, Full</li> <li>• SYSTEM, Full</li> <li>• Domain Computers, Read</li> <li>• ConfigMgr Admins, Full</li> <li>• &lt;Capture User&gt;, Read</li> <li>• &lt;Network Access Account&gt;, Read</li> <li>• &lt;HelpDesk&gt;, Read</li> </ul> |
| <ul style="list-style-type: none"> <li>• <b>Captures</b></li> </ul>   | For all WIM capturing activities  | NTFS: <ul style="list-style-type: none"> <li>• &lt;Capture user&gt;, Full</li> </ul>   |
| <ul style="list-style-type: none"> <li>• <b>Client</b></li> </ul>   | Copy of the Client folder from the ConfigMgr installation directory. All non-push client installs should come from an alternate directory as the initial permissions on the client sub-folder do not allow access to anyone and get changed back to default during site resets. |  |
| <ul style="list-style-type: none"> <li>• <b>Content</b></li> </ul>  | All source files  |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>○ <b>OSD</b></li> </ul> </li> </ul>  |   |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>▪ <b>BootImages</b></li> </ul> </li> </ul> </li> </ul>   |   |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>• <b>(boot.wim)</b></li> </ul> </li> </ul> </li> </ul> </li> </ul> | No sub-folders needed, just each individual, appropriately named .wim file; e.g, MDTBoot(x64).wim   |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>▪ <b>Drivers</b></li> </ul> </li> </ul> </li> </ul>  |   |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>• <b>(Vendor)</b></li> </ul> </li> </ul> </li> </ul> </li> </ul>   | One sub-folder for each vendor; e.g, Dell, HP, Lenovo   |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>○ <b>(Model)</b></li> </ul> </li> </ul> </li> </ul> </li> </ul>    | One sub-folder for each model; e.g, E6510, W520   |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>▪ <b>MDTSettings</b></li> </ul> </li> </ul>  |   |  |

|  |  |  |
|--|--|--|
| <ul style="list-style-type: none"> <li>• <b>(Settings)</b></li> </ul>  | One sub-folder for MDT Settings package; e.g, Deploy, Build and Capture  |  |
| <ul style="list-style-type: none"> <li>▪ <b>MDTToolkit</b></li> </ul>  | Source files for MDT Toolkit Package   |  |
| <ul style="list-style-type: none"> <li>▪ <b>OSImages</b></li> </ul>  |  |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>• <b>(image.wim)</b></li> </ul> </li> </ul>   | No sub-folders needed, just each individual, appropriately named .wim file; e.g, Win7EntSP1(x64).wim                                     |  |
| <ul style="list-style-type: none"> <li>▪ <b>OSInstall</b></li> </ul>   |  |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>• <b>(OS Source)</b></li> </ul> </li> </ul>   | One sub-folder for each Windows version, edition, and architecture; e.g, Win 7 Ent SP1 (x64)   |  |
| <ul style="list-style-type: none"> <li>○ <b>Software</b></li> </ul>  |  |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>▪ <b>(Vendor)</b></li> </ul> </li> </ul>  | One sub-folder for each vendor; e.g., Adobe, Microsoft, Altova   |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>• <b>(Product)</b></li> </ul> </li> </ul> </li> </ul>   | One sub-folder for each vendor's product; e.g., Flash, Office, 7-Zip   |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>○ <b>(Version)</b></li> </ul> </li> </ul> </li> </ul> </li> </ul>   | One sub-folder for each product's different versions, editions, or architectures; e.g., 2010 Pro Plus (x64), 9.2 (x64), 10 (x86) - App-V |  |
| <ul style="list-style-type: none"> <li>○ <b>Updates</b></li> </ul>   |  |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>▪ <b>(Grouping)</b></li> </ul> </li> </ul>  | One sub-folder for each update grouping; e.g., 2010, 2010-1, Win 7   |  |
| <ul style="list-style-type: none"> <li>• <b>ErrorLogs</b></li> </ul>   | A place for startup scripts to dump their error logs   | NTFS: <ul style="list-style-type: none"> <li>• Domain Computers, Full</li> </ul> |
| <ul style="list-style-type: none"> <li>• <b>Import</b></li> </ul>  | Location to import content from (not to) – this is not the location for package source files   |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>○ <b>App-V</b></li> </ul> </li> </ul>   | App-V (only necessary in ConfigMgr 2007)   |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>▪ <b>(Vendor)</b></li> </ul> </li> </ul> </li> </ul>  | One sub-folder for each vendor; e.g., Adobe, Microsoft, Altova   |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>• <b>(Product)</b></li> </ul> </li> </ul> </li> </ul> </li> </ul>   | One sub-folder for each vendor's product; e.g., Flash, Office, 7-Zip   |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>○ <b>(Version)</b></li> </ul> </li> </ul> </li> </ul> </li> </ul> </li> </ul> | One sub-folder for each product's different versions, editions, or architectures; e.g., 2010 Pro Plus (x64), 9.2 (x64), 10 (x86)         |  |
| <ul style="list-style-type: none"> <li>○ <b>Baselines</b></li> </ul>   | DCM/Settings Management baselines downloaded, created with other tools (like CPStudio), or from other sources                            |  |
| <ul style="list-style-type: none"> <li>○ <b>Drivers</b></li> </ul>   | Driver import location   |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>▪ <b>(Vendor)</b></li> </ul> </li> </ul>  | One sub-folder for each vendor; e.g, Dell, HP, Lenovo  |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>• <b>(Model)</b></li> </ul> </li> </ul> </li> </ul>   | One sub-folder for each model; e.g, E6510, W520  |  |
| <ul style="list-style-type: none"> <li>○ <b>MOFs</b></li> </ul>  | Reports, collections, queries, etc. (only necessary in ConfigMgr 2007)   |  |
| <ul style="list-style-type: none"> <li>• <b>InstallationUpdates</b></li> </ul>   | Location for updates downloaded during initial installation and service pack upgrades  |  |
| <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>○ <b>(Version)</b></li> </ul> </li> </ul>   | Release level of downloaded installation files; e.g., RTM, SP1, SP2  |  |

|   |  |   |
|---|--|---|
| <ul style="list-style-type: none"> <li>• <b>MDTLogs</b></li> </ul>      | MDT log files  | NTFS: <ul style="list-style-type: none"> <li>• Network Access Account, Read</li> </ul>      |
| <ul style="list-style-type: none"> <li>• <b>Scripts</b></li> </ul>      | Script repository  |   |
| <ul style="list-style-type: none"> <li>• <b>StateCapture</b></li> </ul> |  | Permissions automatically controlled by ConfigMgr once you designate this folder for an SMP |
| <ul style="list-style-type: none"> <li>• <b>Stuff</b></li> </ul>        | Downloads, other stuff                                     |   |
| <ul style="list-style-type: none"> <li>• <b>Tools</b></li> </ul>        | PSTools, Trace32, Trace64, PolicySpy, CMTrace, other tools |   |